

Lubricants for industry.

Circulating R&O 100



High-quality, universal use lubricant for industrial circulation and bearing systems, type "R&O" (protection against rust and oxidation).

> Use

- Product formulated with specially selected paraffinic base oils and additivation to provide the product with the properties required for its multiple applications.
- Suitable for use in all types of circulation lubrication systems without major requirements, as well as in reducers, speed variators (that do not require a specific oil), and bearings under normal load and temperature conditions, and in reciprocating compressors under normal operating conditions (non-severe).
- Also suitable for steam, hydraulic and gas turbines operating at low temperatures and in hydraulic circuits where special anti-wear properties are not required.

> Benefits

- Due to its anti-rust and anti-corrosion qualities, it has a wide range of applications, reducing the stock of oil in the plant.
- It has adequate resistance to oxidation, and thermal and chemical stability.
- It avoids premature deterioration of gaskets and elastomers.
- Fluidity and high lubricity in boundary lubrication conditions.
- Good demulsibility (water separation) and resistance to foaming.
- Long service life with resulting savings in component lubrication.

> Specifications

- DIN 51524 Part 1 (HL)
- DIN 51515 Part 1 (L-TD)
- DIN 51517 (CL)
- ISO 6743-2 FC

> Physical and chemical properties

Parameter	Units	Method	Circulating R&O 100
ISO Grade	-	-	100
Density at 15 °C	Kg/l	ASTM D-4052	0.889
Flash Point, COC	°C	ASTM D-92	264
Pour Point	°C	ASTM D-5950	-18
Viscosity at 40°C	cSt	ASTM D-445	95
Viscosity at 100°C	cSt	ASTM D-445	10.9
Viscosity index	-	ASTM D-2270	98
Rust prevention (Proc. A)	-	ASTM D-665	Pass

> Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.