

Lubricants for industry.

Blamedol T-15

Technical-grade white medical lubricant



Nonfood Compounds
Program Listed H1&3H
Registration No. 156958



> Use

- Technical-grade white medical lubricant for use in all production processes requiring a non-additive medical white lubricant.
- In general, this product is recommended for use where low toxicity is required due to indirect or accidental contact with food and where compliance with pharmacopoeia specifications is not required.
- Recommended for use in the food industry, animal feed industry, textiles, insecticides, rubber, cork specialties, plastics, precision instruments, etc.

> Benefits

- Stability against light and heat.
- High viscosity index.
- Harmless when handling.
- Concentrations of utilization according to FDA recommendations.
- Compatible with mineral oil.
- Recommended for use in applications where accidental contact with food may occur or be present.

> Specifications

- NSF Nonfood Compounds Registration (H1)
- FDA 21 CFR 178.3620 (b)

> Physical and chemical properties

| Parameter | Units | Method | Blamedol T-15 |
|-------------------------|-------|---------------------|---------------|
| ISO Grade | - | - | 15 |
| Density at 15 °C | kg/l | ASTM D-1298 | 15 |
| V/A flash point, min. | °C | ASTM D-92 | 0.85 |
| Pour point, max. | °C | ASTM D-97 | 180 |
| Viscosity at 40°C | cSt | ASTM D-445 | -9 |
| Ultra-violet absorption | - | 21 CFR 178.3620 (b) | 15 |

> Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.