



MOTOR VEHICLE LUBRICANT OILS. PASSENGER CARS

CEPSA GENUINE 25W50 HIGH MILEAGE 🗐 🚍

DESCRIPTION

High-performance lubricant formulated with Premium bases, designed to combat the effects of ageing on engines with over 100,000 km on the clock, with additives that help prevent oil leaks caused by engine wear, thus prolonging the engine's life.

PRODUCT APPLICATIONS

- High performance oil recommended for all types of saloon cars, especially those with high mileage, in normal or heavy service (in urban or demanding motorway driving).
- Suitable for vehicles with a high oil consumption due to high mileage.
- Suitable for turbocharged or naturally aspirated vehicles especially overloaded by high temperatures.
- Recommended for either gasoline or diesel engines without particulate filters.

PRODUCT USES

- Its high viscosity and extremely low volatility permits reduced levels of oil consumption caused by wear of the engine's moving parts, maintaining a protective film even in the toughest conditions.
- It exceeds the protection requirements of all petrol and diesel engines that recommend an API SL or lower category.
- It has a high detergent and dispersant power, preventing the formation of deposits in the crankcase and pistons, and lacquers or varnishes in the motor sleeves.
- Excellent oxidation (thickening) and thermal stability, meaning the oil can withstand many kilometres at high crankcase temperatures (150°C) without deteriorating.

SPECIFICATIONS

API SL/CF

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	GENUINE HIGH MILEAGE
SAE Grade	-	-	25W50
Density at 15°C	g/ml	ASTM D 4052	0.898
Viscosity at 100°C	cSt	ASTM D 445	19.3
Viscosity at 40°C	cSt	ASTM D 445	191
Viscosity index	-	ASTM D 2270	115
CCS viscosity at -10°C	сР	ASTM D 5293	<13000
Freezing point	°C	ASTM D 5949	-27
Flash point, V/A	°C	ASTM D 92	228
Base number, TBN	mg KOH/g	ASTM D 2896	10.7
Sulphated ash	% (m/m)	ASTM D 874	1.4
HTHS viscosity at 150°C	сР	ASTM D 4683	>3.7

HEALTH & SAFETY AND ENVIRONMENT

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product in accordance with the applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee. These values may be modified without any prior warning.