

STATEMENT OF CHARACTERISTICS

Nº. **C60B3 TER**

1. Name and identification code:

Cationic bituminous emulsion
ADHERMUL XD
C60B3 TER



2. Name and address of manufacturer:

Moeve Client Solutions, SAU
Pº de Castellana, nº 259 A
28046 Madrid (Spain)
Tel.: + 34 91 337 60 00
<https://www.moeve.es/es/utilidades/catalogo/asfaltos/marcado-ce>

3. Expected use:

Tack coat asphalt

4. Characteristics performance assessment and verification system: 2+

5. Notified body:

- AENOR 0099
- Task carried out: On-site factory assessment
- Certificates: 0099/CPR/B11/0210 – Issue date: 30/7/2010
0099/CPR/B11/0216 – Issue date: 30/7/2010

6. Stated characteristics:

| Essential characteristics | Features | Harmonised technical specifications |
|--|----------|-------------------------------------|
| Emulsion | | EN 13808:2023 |
| Creep time (2mm at 40°C) (EN 12846-1) | Class 3 | |
| Break index (EN 13075-1) | Class 3 | |
| Recovered binder (EN 13074-1) | | |
| Consistency at intermediate service temperatures | | |
| Penetration at 25°C (EN 1426) | Class 2 | |
| Consistency at high service temperatures | | |
| Softening point (EN 1427) | Class 3 | |
| Stabilized binder (Stage I Durability) (EN 13074-2) | | |
| Consistency at intermediate service temperatures | | |
| Penetration at 25°C (EN 1426) | Class 2 | |
| Consistency at high service temperatures | | |
| Softening point (EN 1427) | Class 3 | |



- The characteristics of the product identified in point 1 are in compliance with those declared in point 6.
- This statement of characteristics is issued under the sole responsibility of the manufacturer mentioned in point 2.
- Signed by and in representation of the manufacturer:

María González González
Head of Asphalt Technical department
Moeve Client Solutions, SAU

Madrid, June 1, 2026

FIRMADO por: MARIA GONZALEZ GONZALEZ (NIF: 50877056K)
Versión imprimible con información de firma generado desde VALIDe (<http://valide.redsara.es>)
Firma válida.