



DECLARATION OF PERFORMANCE

Nº. **PMB 45/80-75**

1. Name and identity code:

Bitumen for paving
ELASTER RAF BT Additive
PMB 45/80-75



2. Name and address of manufacturer:

Moeve Client Solutions, SAU
Pº de Castellana, nº 259 A
28046 Madrid (España)
Tel.: 91 337 60 00
<https://www.moeve.es/es/utilidades/catalogo/asfaltos/marcado-ce>

3. Applications:

Construction and maintenance of roads, aerodromes and other paved areas
(sealed against penetration)

4. System of assessment and verification of performance compliance: 2+

5. Notified body:

- AENOR 0099
- Task performed: Factory control assessment
- Certificates: 0099/CPR/B11/0203 – Date issued: 30/07/2010
0099/CPR/B11/0208 - Date issued: 30/07/2010

6. Declared performance:

Essential characteristics	Performance	Harmonised technical specifications
Consistency at intermediate service temperatures		EN 14023:2010
Penetration at 25°C (EN 1426)	Class 4	
Consistency at high service temperatures		
Softening point (EN 1427)	Class 3	
Cohesion		
Force-Ductility (traction at 50 mm/min) (EN 13589)	Class 2	
Durability. Resistance to hardening (EN 12607-1)		
Retained penetration (EN 1426)	Class 7	
Increase in softening point (EN 1427)	Class 3	
Mass change (EN 12607-1)	Class 5	
Brittleness at low service temperatures		
Fraass breaking point (EN 12593)	Class 7	
Flash point (EN ISO 2592)	Class 3	
Elastic recovery		
Elastic recovery at 25°C (EN 13398)	Class 2	



- The performance of the product declared in point 1 is in conformity with the declared performance in point 6.
- This declaration of performance is issued at the sole responsibility of the manufacturer identified in point 2.
- Signed by and on behalf of the manufacturer by:

María González González
Head of Asphalt Technical department
Moeve Client Solutions, SAU

Madrid, June 1, 2026