

STATEMENT OF CHARACTERISTICS

Nº. **C60B5 REC**

**1. Name and identification code:**

Cationic bituminous emulsion  
RECIEMUL C  
C60B5 REC



**2. Name and address of manufacturer:**

Moeve Client Solutions, SAU  
Pº de Castellana, nº 259 A  
28046 Madrid (Spain)  
Tel.: 91 337 60 00  
<https://www.moeve.es/en/utilities/catalogue/asphalts/ce-marking>

**3. Expected use:**

Warm recycling with emulsion

**4. Characteristics performance assessment and verification system: 2+**

**5. Notified body:**

- AENOR 0099
- Task carried out: On-site factory assessment
- Certificates: 0099/CPR/B11/0216 – Issue date: 30/7/2010

**6. Stated characteristics:**

Essential characteristics	Features	Harmonised technical specifications
<b>Emulsion</b>		EN 13808:2023
Creep time (2mm at 40°C) (EN 12846-1)	Class 4	
Effect of water on the adhesive properties of the bonding agent (adhesion) (EN 13614)	Class 3	
Break value (EN 13075-1)	Class 5	
<b>Recovered binder (EN 13074-1)</b>		
<b>Consistency at intermediate service temperatures</b>		
Penetration at 25°C (EN 1426)	Class 5	
<b>Consistency at high service temperatures</b>		
Softening point (EN 1427)	Class 8	
<b>Stabilized binder (Stage I Durability) (EN 13074-2)</b>		
<b>Consistency at intermediate service temperatures</b>		
Penetration at 25°C (EN 1426)	Class 4	
<b>Consistency at high service temperatures</b>		
Softening point (EN 1427)	Class 7	



- The characteristics of the product identified in point 1 are in compliance with those declared in point 6.
- This statement of characteristics is issued under the sole responsibility of the manufacturer mentioned in point 2.
- Signed by and in representation of the manufacturer:

María González González  
Head of Asphalt Technical department  
Moeve Client Solutions, SAU

Madrid, June 1, 2026

FIRMADO por: MARIA GONZALEZ GONZALEZ (NIF: 50877056K)  
Versión imprimible con información de firma generado desde VALIDe (<http://valide.recsara.es>)  
Firma válida.