

CEPSA EUROTECH MS 10W30



Descripción



All-purpose lubricant with semi-synthetic technology and fuel-saving properties for heavy diesel engines. Its low ash, phosphorus and sulphur content (Mid-SAPS) means it is ideal for minimising obstruction of particulate filters (DPF/FAP) and preventing the deterioration of post-treatment systems. It is specially designed to exceed the demands of Euro V and VI engines and is also suitable for use in previous engine types.

Applications

- It is suitable for trucks, light commercial vehicles and trailers equipped with particulate filters, as well as for those vehicles without these filters, especially for urban or mixed use.
- Recommended for almost all types of trucks and buses, offering an ideal lubrication solution for mixed fleets of vehicles.
- For agricultural and construction vehicles requiring an oil that offers these features.

Product characteristics

- Excellent rust resistance, prolonging the lifespan of the oil*.
- Provides fuel savings of up to 1% compared to traditional oils.
- The high level of protection and elimination of deposits provided by this oil allows the engine to be kept fully operational, prolonging its lifespan and allowing it to work under optimum conditions.

**Always follow vehicle manufacturer guidelines*

Niveles de Calidad

- | | | | |
|-------------------|--------------------|----------------------------|-----------------------|
| • ACEA E9-12 | • API CJ-4 | • VOLVO VDS-4 | • RENAULT RLD-3 |
| • MB-228.31 | • MAN M 3575 | • MACK EO-O Premium Plus | • MTU Type 2.1 |
| • CAT ECF-3/2/1-a | • CUMMINS CES20081 | • Detroit Diesel DDC93K218 | • Deutz DQC III-10 LA |

Características Típicas

| CHARACTERISTICS | UNITS | METHOD | CEPSA EUROTECH MS 10W30 |
|------------------------|----------|----------------|-------------------------|
| SAE Grade | - | - | 10W30 |
| Density at 15°C | g/ml | ASTM D 4052 | 0,866 |
| Viscosity at 100°C | cSt | ASTM D 445 | 11,2 |
| Viscosity at 40°C | cSt | ASTM D 445 | 74,6 |
| Viscosity index | - | ASTM D 2270 | 141 |
| CCS viscosity at -25°C | cP | ASTM D 5293 | 6100 |
| Pour point | °C | ASTM D 97/5950 | -42 |
| Flash point V/A | °C | ASTM D 92 | >200 |
| Base number, TBN | mg KOH/g | ASTM D 2896 | 9,0 |
| Sulphated ash | % (m/m) | ASTM D 874 | <1,0 |

Seguridad, Higiene y Medio Ambiente

The product has a safety data sheet pursuant to current legislation, which offers information regarding the hazardous nature of the product, handling precautions and first aid and environmental measures.

The values of the typical characteristics shown in the table are average values. They are used by way of illustration and do not represent a guarantee. These values are subject to change without prior notice being given.