

Disprimer

Asphalt paint consisting of modified bitumen and aromatic solvents, which provides excellent protection for all surfaces.

Applications:

- › Priming surfaces for subsequent waterproofing
- › Protection of metallic structures
- › Superficial waterproof protection for buried concrete elements
- › Protection of buried concrete elements

Properties:

- › Easy to apply
- › Easy to handle
- › Good adherence to the substrates
- › Inflammable

Specifications:

Characteristics	Units	Standard	Min.	Max.
Brookfield viscosity at 25°C	mPa.s	NIE-008	100	300
Inflammability	°C	UNE 104281-1.12	25	-
Density at 25°C		UNE 104281-5.4	0,92	0,96
Non - volatile material	%	UNE 104281-3.7	48	52
Volatile organic compounds	g/l	ISO 11890-1	-	500
Characteristics of the residue				
Dry to touch at 25°C and 50% Hr	h	UNE 104281-5.13	-	1
Dry for repainting at 25°C and 60% Hr	h	UNE 104281-5.13	-	24

Disprimer

Instructions for use:

- › The support upon which Disprimer is to be applied should have a clean, adherent surface free of dust and other substances (oils, lime, etc.) which might affect adherence or reduce the product's properties. It is advisable to sandblast the support to clean it
- › Mix the product in its container before applying it
- › Apply with a spray gun, brush or roller
- › Let each coat dry before applying the next coat

Other recommendations:

- › The product should be applied at temperatures of between 5°C - 35°C and should not be applied in bad weather
- › Since the paint contains solvents, it should be applied in ventilated places using EPIs
- › If necessary, solvents can be added to thin it
- › The area treated should be protected from direct sunlight.
- › Disprimer is not suitable for applications where it would be in contact with solvents or fuels

Storage:

- › The containers should be kept somewhere where they are protected from both frost and overexposure to the sun
- › Storage temperatures should not be below 5°C since this could affect the quality of the product
- › After use, tightly seal the containers to prevent evaporation of the solvent and the corresponding increase in the viscosity of the paint
- › Keep away from fire
- › The maximum storage time recommended is 12 months from the manufacturing date in the original containers, undamaged and tightly closed