

CEPSA TRUCK XTRA LIFE 25W60

Description



Engine oil for high performance, high viscosity, heavy-duty diesel applications formulated with seal conditioners and intended for use in engines where the demands of high mileage or operation in hot climates can degrade seals leading to increased oil consumption.

Applications

- Designed for use in "Heavy-Duty Diesel" applications in both naturally aspirated and turbocharged engines.
- Suitable for Light, Medium and Heavy vehicles that require a "high performance" oil to prevent build-up of soot and thickening of oil in the crankcase.
- Suitable in cases that require a very high viscosity oil as a result of increased oil consumption or operation in severe load and temperature conditions.
- Suitable for use in civil works and mining vehicles that require a low consumption lubricant.

Performance

- Formulated with seal conditioner additives that restore the elasticity of gasket and seal materials, thereby preventing possible oil leaks caused by cracking.
- Superior wear-reducing protection in all areas of the engine, especially in areas subjected to high operating temperatures where there is a greater risk of breaking the lubrication film.
- Suitable for use in hot climates and in the most demanding conditions.
- The superior detergent and dispersal power prevents the formation of sludge in the crankcase, keeping the engine clean.

Quality Levels

· API CH-4
· MAN 3275-1

· ACEA E7/E5
· Volvo VDS-2

· MB 228.3
· MTU Type 2

Typical Characteristics

| CHARACTERISTICS | UNITS | METHOD | CEPSA TRUCK XTRA LIFE |
|------------------------|----------|------------------|-----------------------|
| SAE Grade | - | - | 25W60 |
| Density at 15°C | g/ml | ASTM D 4052 | 0,8992 |
| Viscosity at 100°C | cSt | ASTM D 445 | 24,2 |
| Viscosity at 40°C | cSt | ASTM D 445 | 253 |
| Viscosity index | - | ASTM D 2270 | 120 |
| CCS viscosity at -10°C | cP | ASTM D 5293 | <13000 |
| Pour point | °C | ASTM D 5950 / 97 | -15 |
| Flash point V/A | °C | ASTM D 92 | >200 |
| Base number, TBN | mg KOH/g | ASTM D 2896 | 11 |
| Sulphated ash | % (m/m) | ASTM D 874 | 1,2 |

Health & Safety and Environment

In accordance with legislation in force, this product has the corresponding Material Safety Data Sheet, which provides information about potential hazards, handling precautions and first aid measures, together with available environmental data.

The values for typical characteristics shown in the table are average values provided for information purposes only, and they do not constitute a guarantee. These values may be changed without prior notice.