

## LUBRICANTS FOR INDUSTRIAL USE

### CEPSA LICENA HS-95

#### DESCRIPTION

Hydraulic safety fluid oil in water emulsion type (HFAE) with high resistance to bacteria. This product is highly water soluble and fire resistant, and its properties allow for very specific applications.

#### PRODUCT APPLICATIONS

- Special applications in hydraulic systems for presses in wood industry with specific safety requirements.
- For applications in the mining sector with flame retardant and corrosion protection requirements.

#### PRODUCT PERFORMANCE

- Exceptional bacterial resistance.
- Good anticorrosion and antirust properties.
- Does not form deposits.
- Does not attack joints or paintings.

#### SPECIFICATIONS

- ISO 12922 type HFAE

#### TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA LICENA HS-95	
<b>*Concentrate</b>				
Aspect	-	Visual	Transparent Reddish Brown	
Storage stability	-	Visual	Stable	
- 24 hours at 40°C			Stable	
- 7 days at 25°C				
<b>*5% Emulsion in water</b>			<b>At 20TH</b>	<b>Distilled</b>
Aspect	-	Visual	Whitish	
Storage stability	-	Visual	Stable	Stable
- 24 hours at 40°C			Stable	Stable
- 7 days at 25°C				
pH	-	DIN 51369	9.1	9.0
Foam	-	CNOMO 655212	Pass	Pass
Herbert Test	-	DIN 51360/1	0/0-0	0/0-0
Paper Filter Test	-	DIN 51360/2	0	0
<b>*3% Emulsion in distilled water</b>				
Herbert Test	-	DIN 51360/1	0/0-0	
Paper Filter Test	-	DIN 51360/2	1	

#### HEALTH & SAFETY AND ENVIRONMENT

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.