

Automotive lubricants. Automatic transmissions.

ATF 70



Key information

- A lubricant formulated with specially selected base stocks and a high-performance additive package for automatic transmissions (ATF).
- Automatic transmissions that require the General Motors Dexron III specification.

› Manufacturer specifications

- GM Dexron III
- Allison C-4
- DTFR 13C170 (MB 236.9)
- ZF 04D/14A (ZF001939)
- CAT TO-2
- MAN 339 Z1/V1
- Voith H55.6335.xx

› Use

- Automotive automatic transmissions that require General Motors Dexron III fluid.
- Automatic transmissions in passenger cars and heavy-duty vehicles.
- Power steering mechanisms and automotive hydraulic systems.

› Benefits

- Excellent fluidity at very low temperatures.
- Maximum protection of planetary gears and torque converter
- Excellent resistance to oxidation, ensuring long service life.
- Enables smooth and progressive gear shifts at any operating speed.
- Optimal protection for all components of automatic transmissions, torque converters, manual transmissions, and hydraulic systems.

› Physical and chemical properties

Characteristic	Units	Method	ATF 70
Color	-	Visual	Red
Density at 15°C	kg/l	ASTM D 4052	0.860
Viscosity at 100°C	cSt	ASTM D 445	7.7
Viscosity at 40°C	cSt	ASTM D 445	38
Viscosity Index	-	ASTM D 2270	175
Brookfield viscosity at -40°C	cP	ASTM D 2983	<50,000
Pour Point	°C	ASTM D 5950	-45
Flash Point	°C	ASTM D 92	202

› Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The values of typical characteristics listed in the table are average values provided for informational purposes only and do not constitute a guarantee. These values are subject to change without notice.

Moeve Client Solutions S.A.U. • Paseo de la Castellana, 259A • 28046 Madrid • moeve.es

Rev.00, month: July, year: 2026