

Automotive lubricants. Off-Road transmissions.

Auriga TA 40



Key information

- Lubricant formulated with highly refined bases and additives that give it excellent properties in its specific application.

> Quality standards

- SAE 10W
- API CF, SF

> Manufacturer specifications

- CATERPILLAR TO-2
- Allison C-3

> Use

- Auriga TA 40 oil is specially formulated for use in torque converters and hydraulic transmissions that require a fluid of this nature.

> Benefits

- High level of protection against friction.
- High oxidation resistance.
- Excellent compatibility with seals and gaskets.
- Long duration in service.
- Excellent protection of all the organs of the torque converters.

> Physical and chemical properties

Characteristic	Units	Method	Auriga TA 40
SAE Grade	-	-	10 W
Density at 15°C	kg/l	ASTM D 4052	0.881
Viscosity at 100°C	cSt	ASTM D 445	6.3
Viscosity at 40°C	cSt	ASTM D 445	40.3
Viscosity Index	-	ASTM D 2270	104
Pour Point	°C	ASTM D 5950	-30
Flash Point	°C	ASTM D 92	258

> Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.