

Automotive lubricants. Off-road Transmissions.

Auriga UTTO 55 10W-30



Key information

- This multi-grade universal tractor transmission oil (UTTO) uses the latest technology and meets the requirements of the most modern agricultural equipment. It is suitable for use in wet brakes, hydraulic systems, clutches and torque converters.

> Quality standards

- API GL-4
- ISO L-C/H

> Manufacturer specifications

- | | | |
|-----------------------|---------------------------------------|-------------------------------------|
| • JDM J20C/D | • ZF TE-ML 03E/05F/17E/21F (ZF001200) | • Kubota UDT |
| • CATERPILLAR TO-2 | • CNH MAT 3525/3540 | • FNHA-2D-201.00 (ex FORD M2C 134D) |
| • Allison C-4 | • New Holland/FNHA-2C-201.00 | • Ford M2C 86B,86C |
| • Volvo 97303 (WB101) | • MF CMS M1135/M1141/M1143/M1145 | • Case MS 1204,1206,1207,1209 |

> Use

- Suitable for transmissions, differentials, and hydraulic systems subjected to high loads and severe operating conditions.
- Recommended for equipment requiring high protection against wear, corrosion, rust, and foaming, while also ensuring good performance at low temperatures and compatibility with sealing materials.

> Benefits

- Reduces the formation of sludge, lacquer, and varnish.
- High load-carrying capacity.
- Excellent lubrication across all operating conditions.
- Immediate oil circulation upon startup.
- Eliminates vibrations and squeaking in oil-immersed brakes.
- Protects metal surfaces from chemical attack.
- Prevents seal deterioration.

> Physical and chemical properties

Characteristic	Units	Method	Auriga UTTO 55 10W-30
SAE Grade	-	-	10W-30
Density at 15°C	kg/l	ASTM D 4052	0.885
Viscosity at 100°C	cSt	ASTM D 445	9.4
Viscosity at 40°C	cSt	ASTM D 445	54.4
Viscosity Index	-	ASTM D 2270	156
Pour Point	°C	ASTM D 5950	-33
Flash Point	°C	ASTM D 92	210

> Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.