

Automotive lubricants. Off-road Transmissions.

Auriga UTTO 85



Key information

- A UTTO-type multifunctional lubricant specially developed for the axles of earth-moving machinery and heavy off-road equipment with oil-immersed axles.

> Quality standards

- API GL-4

> Manufacturer specifications

- FORD M2C86-B
- MF CMS 1135

> Use

- Recommended for systems that require high protection against wear, corrosion, and rust.
- Suitable for demanding service conditions, thanks to its high oxidation stability, foam resistance, good fluidity at low temperatures, and compatibility with sealing materials.

> Benefits

- Reduces the formation of sludge, lacquer, and varnish, keeping the system cleaner.
- Provides high load-carrying capacity and protection against wear.
- Ensures effective lubrication under all operating conditions.
- Facilitates cold starts and eliminates vibrations and squeaking in wet brakes.

> Physical and chemical properties

Characteristic	Units	Method	Auriga UTTO 85
Density at 15°C	kg/l	ASTM D 4052	0.892
Viscosity at 100°C	cSt	ASTM D 445	10.9
Viscosity at 40°C	cSt	ASTM D 445	84.3
Viscosity Index	-	ASTM D 2270	116
Pour Point	°C	ASTM D 5950	-30
Flash Point	°C	ASTM D 92	252
Copper Corrosion	-	ASTM D 130	1b

> Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The values of typical characteristics listed in the table are average values provided for informational purposes only and do not constitute a guarantee. These values are subject to change without notice.

Moeve Client Solutions S.A.U. • Paseo de la Castellana, 259A • 28046 Madrid • moeve.es

Rev.00, month: July, year: 2026