

Automotive lubricants. Manual transmissions

Driveline 75W-80



Key information

- A lubricant specially developed for the lubrication of manual transmissions in passenger cars.
- It offers high thermal stability, meeting the needs of leading automakers.

> Quality standards

- API GL-4
- API MT-1

> Use

- Manual gearboxes, synchronized or not.
- Adequate performance over a wide range of temperatures.
- Steering mechanisms and reducers in automobiles.
- Suitable for filling in boxes where GL-4 oils are required.

> Benefits

- Excellent protection against wear and heavy loads.
- High resistance to oxidation, high temperatures, and foaming.
- Effective protection against corrosion, rust, and chemical attack.
- Optimal lubrication and compatibility with gaskets and sealing materials.

> Physical and chemical properties

Characteristic	Units	Method	Driveline 75W-80
SAE Grade	–	–	75W80
Density at 15°C	kg/l	ASTM D 4052	0.885
Viscosity at 100°C	cSt	ASTM D 445	8.4
Viscosity at 40°C	cSt	ASTM D 445	49.9
Viscosity Index	-	ASTM D 2270	144
Brookfield viscosity -40°C	cSt	ASTM D 2983	120000
Pour Point	°C	ASTM D 5950	-42
Flash Point	°C	ASTM D 92	204

> Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The values of typical characteristics listed in the table are average values provided for informational purposes only and do not constitute a guarantee. These values are subject to change without notice.

Moeve Client Solutions S.A.U. • Paseo de la Castellana, 259A • 28046 Madrid • moeve.es

Rev.00, month: July, year: 2026