

Automotive lubricants. 4-stroke motorcycle engine.

Emotion Full 4T 20W-50




Key information

- High-performance lubricant for 4-stroke motorcycles used for city and highway riding.
- Especially suitable for “V-Twin” twin-cylinder engines.
- Optimal protection for the engine, transmission, and clutch.

> Quality standards

- API SL
- JASO MA2



JASO T 903: 2016
EL RENDIMIENTO ESTÁ GARANTIZADO por
Moeve Client Solutions S.A.U.

> Use

- Recommended for 4-stroke motorcycles of any displacement and performance level, as well as for heavy-duty riding.
- Especially suitable for motorcycles with a shared lubrication system for the engine, transmission, and wet clutch. It is also suitable for motorcycles equipped with a dry clutch.
- It is recommended to follow the indications of the motorcycle manual regarding viscosity and oil specifications, as well as its drain interval according to the amount of sulfur of the fuel used.

> Benefits

- Its high detergency ensures excellent piston cleaning.
- Provides adequate protection during startup and excellent lubricant film protection at high temperatures.
- Maintains excellent lubrication year-round, ensuring maximum protection against engine seizure.
- Protects the gears in the transmission, minimizing clutch plate slippage and power loss.

> Physical and chemical properties

Characteristic	Units	Method	Emotion Full 4T 20W-50
SAE Grade	-	-	20W-50
Density at 15°C	kg/l	ASTM D 4052	0.892
Viscosity at 100°C	cSt	ASTM D 445	18.81
Viscosity at 40°C	cSt	ASTM D 445	167
Viscosity Index	-	ASTM D 2270	127
Pour Point	°C	ASTM D 5950	-27
Flash Point	°C	ASTM D 92	244
Base number, TBN	mg KOH/g	ASTM D 2896	6.7
Kinematic viscosity at 100 °C after shear stability test	cSt	ASTM D 6278	17.22

> Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.