

Automotive lubricants.

Power Steering



Key information

- Hydraulic lubricant formulated with mineral paraffinic bases and high-performance additives that provide protection against wear and friction. It is specially designed for power steering and hydraulic system applications, promoting circuit cleanliness, proper equipment operation, and the preservation of seals and gaskets.

› Use

- Hydraulic fluid for power steering and power transmission systems, designed to provide efficient operation in a wide variety of industrial equipment.
- Highly effective anti-wear protection, thanks to its zinc-based additives, although it is not recommended for equipment containing silver components or alloys.

› Benefits

- Excellent protection against pump wear.
- Prevents deterioration of seals and gaskets.
- High filterability in the presence of water.
- Excellent protection for non-ferrous metals, even in the presence of water.
- High resistance to oxidation and excellent thermal stability against rust and corrosion.

› Physical and chemical properties

Characteristic	Units	Method	Power Steering
Density at 15°C	kg/l	ASTM D 4052	0.871
Viscosity at 100°C	cSt	ASTM D 445	5.17
Viscosity at 40°C	cSt	ASTM D 445	30
Viscosity Index	-	ASTM D 2270	104
Pour Point	°C	ASTM D 5950	-27
Flash Point	°C	ASTM D 92	200

› Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.