

DECLARATION OF PERFORMANCE

JUNTOPLAST C

1. Name and identity code

Juntoplast C

N1 type thermal sealing mastic

2. Name and address of manufacturer:

MOEVE COMMERCIAL, SAU

Pº de Castellana, nº 259 A

28046 Madrid (España)

Tel.: 91 337 60 00

<https://www.moeve.es/es/utilidades/catalogo/asfaltos/marcado-ce>

3. Applications:

Hot-applied product for sealing cracks in roads, airports, bridge decks, car park floors, etc.

4. System of assessment and verification of performance compliance: 4**5. Declared performance: Type N1**

Essential characteristics	Performance	Harmonised technical specifications
Cone penetration at 25°C, 5s, 150g, in 0.1 mm	40-130	EN 14188-1:2005
Softening point in °C	>85	
Density at 25°C in mg/m³	>1.1	
Penetration and recovery (resilience) in %	>60	
Creep in mm	<2	
Stability to heat (168h at 70°C)		
Cone penetration at 25°C, 5s, 150g, in 0.1 mm	40-130	
Penetration and recovery (resilience) in %	>60	



Gerardo Pardo Alvarez-Buylla
Director de Asfaltos
MOEVE COMMERCIAL, SAU

Madrid, 1 de julio de 2025