

LUBRICANTS FOR INDUSTRIAL USE

CEPSA TRONCOIL GAS 40 G

DESCRIPTION

Medium-ash lubricant oil.

Formulated with highly refined, select paraffin base oils, with special, next-generation additives that are very effective at neutralizing acids from combustion.

PRODUCT APPLICATIONS

- Especially recommended for normal-intake or turbocharged four-stroke engines that require medium-ash lubricant oil (ash percentages lower than 0.5%).

PRODUCT PERFORMANCE

- Good alkalinity retention. Superb neutralization of the acids formed by combustion.
- Remarkable resistance to corrosion and foam formation.
- Outstanding nitration and oxidation stability.
- Superb protection against piston and jacket wear.
- Maximum protection of valves and seats.
- Resistant to the formation of carbonaceous residue and deposits.

SPECIFICATIONS

- API CD
- The packet of additives used in its formulation has received approval from the following manufacturers: CATERPILLAR, AJAX, DRESSER-RAND (CLARK), WAUKESHA, JENBACHER, SUPERIOR

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA TRONCOIL GAS 40 G
SAE GRADE	-		40
Density, 15 °C	g/cc	D-4052	0.897
Flash point, COC	°C, min.	D-92	>220
Pour point	°C	D-97	-18
Viscosity at 100 °C	cSt	D-445	13.88
Viscosity at 40 °C	cSt	D-445	135.6
Viscosity index	min.	D-2270	99
Base number	mg KOH/g	D-2896	8.9
Sulfated ash	% p	D-874	0.88

HEALTH & SAFETY AND ENVIRONMENT ENTE

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.