

## MOTORCYCLE LUBRICANTS

## CEPSA MOTO 4T RUTA 66 15W50



## DESCRIPTION

Super multigrade high-performance mineral lubricant oil for four-stroke motorcycles used for city and open-road driving. Complies with the requirements of the main American, European and Japanese four-stroke motorcycle manufacturers.

## PRODUCT APPLICATIONS

- Recommended for four-stroke motorcycles of any capacity and performance, and for driving under severe conditions.
- Suitable for motorcycles with combined lubrication of the engine, gearbox and wet clutch. Also suitable for dry-clutch motorcycles.

## PRODUCT PERFORMANCE

- Its high detergency ensures excellent cleaning of the piston.
- Provides appropriate protection during start-up and high protection of the lubricant film at high temperatures.
- Excellent lubrication at all times of year, ensuring maximum protection against engine seizing.
- Protects the gears in the gear box, minimizing clutch plate slippage and loss of power.

## SPECIFICATIONS

- API SL
- JASO MA2

## TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA MOTO 4T RUTA 66
SAE Grade		---	15W50
Density at 15°C	g/ml	ASTM D4052	0.884
O/C Flash point	°C	ASTM D92	>200
Pour Point	°C	ASTM D5950	-33
Viscosity at 100°C	cSt	ASTM D445	18.99
Viscosity at 40°C	cSt	ASTM D445	145.5
Viscosity Index		ASTM D2270	148
Total Base Number (TBN)	mg KOH/g	ASTM D2896	6.9

## HEALTH &amp; SAFETY AND ENVIRONMENT

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.