MAINTENANCE

AUTOMOBILE MAINTENANCE PRODUCTS

CEPSA DESENGRASANTE

AUTOMATIC AND MANUAL WASH

DESCRIPTION

CEPSA DESENGRASANTE is a green, alkaline, liquid product, totally soluble in both cold and hot water. Specially formulated for cleaning bodywork, underbody and engines in all types of vehicles. Excellent results for truck tarps.

PRODUCT PERFORMANCE

- Its very high sequestering characteristics make its performance optimal in any type of water, avoiding obstructions in nozzles, pipes and pumps.
- CEPSA DESENGRASANTE contains a selection of surfactants that allow the elimination of different degrees of dirt, and it also has a balanced foaming power to allow its use with modern spraying equipment.

INSTRUCTIONS FOR USE

- *On engines and underbody:*

Dilute 5-10% in water, spray on the engine or underbody, leave for 2-5 minutes and rinse with pressurized water.

- *On floors and pits:*

Dilute 15-25% in water, apply over the entire surface to be cleaned, leave for 10-20 minutes and rinse with water.

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA DESENGRASANTE
Appearance	-	Visual	Clear Liquid
Density at 20ºC	kg/l	ASTM D-4052	1.097
Color	-	Visual	Green
Odor	-	-	Odorless
Concentrated pH	-	-	13.3
pH at 1%	-	-	11.1
Ionic Character	-	-	Non-ionic and cationic surfactants
Pour Point	ºC	ASTM D-5950	-2ºC
Active matter	%	-	17.5

HEALTH & SAFETY AND ENVIRONMENT

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee.
These values may be modified without any prior warning.